

Teniski podni sistem za vanjkse i unutrašnje teniske terene, tačkasto elastičan prema EN 14904

SLOJEVI SISTEMA

-  **Boja za linije**
PORPLASTIC X8085 SR
-  **Strukturni završni sloj, obojen, mat**
PORPLASTIC S6085 SR
-  **Filer za asfalt**
VIASOL EP-P285 + pjesak
-  **Prajmer (jedino za beton)**
VIASOL EP – P210
-  **Podloga:** asfalt ili beton



OPIS SISTEMA

- 3-4 sloja sistema za premazivanje
- nepropusan
- bez forlamdehida i pentaklorofenola
- dobra otpornost na grebanje i abraziju
- za VANJSKI i UNUTRAŠNJI
- dostupan u širokoj paleti boja
- lak za čišćenje

PRIMJENA

- teniski tereni vani
- teniski tereni unutra



NANOŠENJE I KORIŠTENJE

slojevi	proizvod	potrošnja (kg/m ²)	debljina (mm)	nanošenje
boja za linije	PORPLASTIC X8085 SR	20 – 30 g po metru za trčanje	0.1- 0.2	valjak ili četka
strukturni završni sloj	PORPLASTIC S6085 SR (2-3 sloja)	2 sloja: 540 g 3 sloja: 900 g	0.3 0.5	gumeni gleter
filer za asfalt	VIASOL EP – P285 + kvarcni pjesak 0.06 -0.2	800-1000	0.1-0.2	izrezana i stavljena u čisto ljepilo gumena lopatica
prajmer	VIASOL EP – P210	oko 0.4	oko 0.2	valjak ili gumeni gleter
substrat	Asfaltni ili cementi substrat prema standardima, bez pukotina i praznina, nosivi, čvrstoće na prionjivost (pull- off) = 1.0 N/mm ² (EN ISO 4624), zadržane vlage u materijalu < 6% CM			



Napomena: za buduće informacije pogledajte tehnički list ili kontaktirajte naš tehnički servis. Svi podaci su u približnim vrijednostima. Kako su svi tehnički listovi popunjavani prema laboratorijskim analizama koje se kontinuirano izvode, korisnik proizvoda treba da provjeri najnovije protokole –odnosno da kontaktira našu tehničku podršku i website: www.tenzo.ba. Svi tehnički podaci su podložni promjenama bez prethodne najave.

Ovlašteni izvođač:

Tehničko tehnološki biro TENZO d.o.o.

Tel: +387 51 323 680

Kralja Petra II 34b, 78000 Banja Luka, BiH

e-mail: info@tenzo.ba

www.tenzo.ba